

Martin

ニュータイプ(ブッシング式)

Martin-Flex[®] Couplings

タイヤカップリング

フレキシブルタイヤ

Flexible Type

Highly resilient flexible tyre cushions shock load between driving and driven machines. Enables high levels of misalignment to be accommodated.

メンテナンスと潤滑

Maintenance and Lubrication

Lubrication no maintenance or lubrication is required, visual inspection is all that is necessary.

取り付け簡単

Easy Installation

Radially split tyre facilitates easy installation and removal without disturbing driving or driven shafts.

テーパーフランジ

Taper Flange

Made from high grade S.G. iron, versatile design enable easy positioning on the shafts. The clamping systems prevents relative movement between flexible tyre and flange.

テーパーブッシュ

Taper Bush

Provide a wide range of bore diameters, and enables easy assembly to shafts.

テンションメンバー
(伝導部)

Tension Member

Cross piled synthetic tension member enables torque to be transmitted in either direction.

ゴム化合物

Elastomeric Compound

Available in either natural rubber or fire-resistant and anti-static chloroprene. Provides the shape and damping of the tyre.



エバオン株式会社

本社 〒542-0064 大阪市中央区上汐 1-1-5

TEL: (06) 6768-1005 (代) FAX: (06) 6764-5539

営業所: 東京・掛川・宇都宮・ホーチミン・上海