



SPZ-6

適用M.3V.3VX.SPZベルト


Unit : mm




18




19




22




24



26



29



32

品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SPZ 90-6	90	94	1610	42		51		25	76	1.6	19
SPZ 95-6	95	99	1610	42		51		25	76	1.8	19
SPZ 100-6	100	104	2012	50		44		32	76	1.8	19
SPZ 106-6	106	110	2012	50		44		32	76	2.1	19
SPZ 112-6	112	116	2012	50			44	32	76	2.4	18
SPZ 118-6	118	122	2517	60		31		45	76	2.3	19
SPZ 125-6	125	129	2517	60		31		45	76	2.8	19
SPZ 132-6	132	136	2517	60			31	45	76	3.3	18
SPZ 140-6	140	144	2517	60			31	45	76	3.9	18
SPZ 150-6	150	154	2517	60			31	45	76	4.7	18
SPZ 160-6	160	164	2517	60			31	45	76	5.6	18
SPZ 170-6	170	174	2517	60			31	45	76	6.4	18
SPZ 180-6	180	184	2517	60			31	45	76	7.4	18
SPZ 190-6	190	194	2517	60		15.5	15.5	45	76	9.3	26
SPZ 200-6	200	204	2517	60		15.5	15.5	45	76	9.9	26
SPZ 212-6	212	216	2517	60	125	15.5	15.5	45	76	7.8	22
SPZ 224-6	224	228	2517	60	125	15.5	15.5	45	76	9.7	22
SPZ 236-6	236	240	2517	60	125	15.5	15.5	45	76	9.4	22
SPZ 250-6	250	254	2517	60	125	15.5	15.5	45	76	11.4	22
SPZ 280-6	280	284	2517	60	124	15.5	15.5	45	76	11.8	22
SPZ 300-6	300	304	2517	60	125	15.5	15.5	45	76	13	22
SPZ 315-6	315	319	2517	60	125	15.5	15.5	45	76	14.8	22
SPZ 355-6	355	359	2517	60	125	15.5	15.5	45	76	17.5	29
SPZ 400-6	400	404	3030	75	150			76	76	19.3	32
SPZ 450-6	450	454	3030	75	150			76	76	21.4	32
SPZ 500-6	500	504	3030	75	150			76	76	24	32
SPZ 630-6	630	634	3535	90	178	6.5	6.5	89	76	40.3	24

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合があります。