




# SPB-8 SPB-10

## 適用B.BX.5V.5VX.SPBベルト

Unit : mm

品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SPB 180-8	180	187	3030	75		41	41	76	158	12	26
SPB 190-8	190	197	3030	75		41	41	76	158	13.3	26
SPB 200-8	200	207	3535	90		34.5	34.5	89	158	14.5	26
SPB 212-8	212	219	3535	90		34.5	34.5	89	158	17.3	26
SPB 224-8	224	231	3535	90		34.5	34.5	89	158	20.1	26
SPB 236-8	236	243	3535	90		34.5	34.5	89	158	23.1	26
SPB 250-8	250	257	3535	90		34.5	34.5	89	158	26.6	26
SPB 280-8	280	287	3535	90	175	34.5	34.5	89	158	26.5	22
SPB 300-8	300	307	3535	90	175	34.5	34.5	89	158	28.7	22
SPB 315-8	315	322	3535	90	175	34.5	34.5	89	158	30.5	22
SPB 335-8	335	342	3535	90	175	34.5	34.5	89	158	33.6	22
SPB 355-8	355	362	3535	90	175	34.5	34.5	89	158	37.6	22
SPB 400-8	400	407	4040	100	210	28	28	102	158	49.3	22
SPB 450-8	450	457	4040	100	210	28	28	102	158	50.6	22
SPB 475-8	475	482	4040	100	210	28	28	102	158	49.6	29
SPB 500-8	500	507	4040	100	210	28	28	102	158	56.5	29
SPB 560-8	560	567	4545	115	240	22	22	114	158	69.6	29
SPB 630-8	630	637	4545	115	240	22	22	114	158	84.5	29
SPB 710-8	710	717	4545	115	240	22	22	114	158	102	29
SPB 800-8	800	807	4545	115	240	22	22	114	158	115	29
SPB 900-8	900	907	4545	115	240	22	22	114	158	118	29
SPB 1000-8	1000	1007	5050	125	265	15.5	15.5	127	158	149	29



SPB 180-10	180	187	3030	75		60	60	76	196	14.8	26
SPB 200-10	200	207	3535	90		53.8	53.2	89	196	17.6	26
SPB 212-10	212	219	3535	90		53.5	53.5	89	196	20.4	26
SPB 224-10	224	231	3535	90		53.5	53.5	89	196	22.7	26
SPB 236-10	236	243	3535	90		53.5	53.5	89	196	25.5	26
SPB 250-10	250	257	3535	90		53.5	53.5	89	196	29.3	26
SPB 280-10	280	287	3535	90	185	53.5	53.5	89	196	30.5	22
SPB 300-10	300	307	3535	90	175	53.5	53.5	89	196	33	22
SPB 315-10	315	322	3535	90	187	53.5	53.5	89	196	37.5	22
SPB 335-10	335	342	4040	100	200	47	47	102	196	41.6	22
SPB 355-10	355	362	4040	100	215	47	47	102	196	47.9	22
SPB 400-10	400	407	4040	100	215	47	47	102	196	54.7	22
SPB 450-10	450	457	4545	115	242	41	41	114	196	63.8	29
SPB 500-10	500	507	4545	115	245	41	41	114	196	72.5	29
SPB 560-10	560	567	4545	115	242	41	41	114	196	78.9	29
SPB 630-10	630	637	4545	115	242	41	41	114	196	93.9	29
SPB 710-10	710	717	4545	115	240	41	41	114	196	112	29
SPB 800-10	800	807	4545	115	240	41	41	114	196	130	29
SPB 900-10	900	907	5050	125	267	34.5	34.5	127	196	162	29
SPB 1000-10	1000	1007	5050	125	267	34.5	34.5	127	196	183	29

\*質量はプーリ単体です。

\*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合です。