



SP8V-4 SP8V-6

適用8Vベルト


Unit : mm




19




20




22




23




26



28



29



31

| 品番 Part No. | データ径 dn | 外径 D | ブッシング Bushing | | ボス部 Hub | | | | リム幅 W | 質量 (kg) | 形状図番 Type |
|----------------|------------|---------|------------------|-------------------|------------|------|-----|-----|----------|------------|--------------|
| | | | 品番 No. | 最大軸穴径 Max.Bore | d | t1 | t2 | l | | | |
| SP8V 300-4 | 295 | 300 | 4040 | 100 | | 21.8 | | 102 | 123.8 | 36.3 | 19 |
| SP8V 315-4 | 310 | 315 | 4040 | 100 | | 21.8 | | 102 | 123.8 | 41.5 | 19 |
| SP8V 335-4 | 330 | 335 | 4040 | 100 | | 21.8 | | 102 | 123.8 | 49 | 19 |
| SP8V 355-4 | 350 | 355 | 4040 | 100 | 210 | 21.8 | | 102 | 123.8 | 43.4 | 28 |
| SP8V 375-4 | 370 | 375 | 4040 | 100 | 210 | 21.8 | | 102 | 123.8 | 46.7 | 28 |
| SP8V 400-4 | 395 | 400 | 4040 | 100 | 210 | 21.8 | | 102 | 123.8 | 51 | 28 |
| SP8V 425-4 | 420 | 425 | 4040 | 100 | 210 | 21.8 | | 102 | 123.8 | 56 | 28 |
| SP8V 450-4 | 445 | 450 | 4545 | 115 | 240 | | 9.8 | 114 | 123.8 | 66.7 | 20 |
| SP8V 475-4 | 470 | 475 | 4545 | 115 | 240 | | 9.8 | 114 | 123.8 | 66 | 31 |
| SP8V 500-4 | 495 | 500 | 4545 | 115 | 240 | | 9.8 | 114 | 123.8 | 69.7 | 31 |
| SP8V 560-4 | 555 | 560 | 4545 | 115 | 240 | | 9.8 | 114 | 123.8 | 79.7 | 31 |
| SP8V 630-4 | 625 | 630 | 4545 | 115 | 240 | | 9.8 | 114 | 123.8 | 91.8 | 31 |
| SP8V 710-4 | 705 | 710 | 4545 | 115 | 240 | | 9.8 | 114 | 123.8 | 108 | 31 |
| SP8V 800-4 | 795 | 800 | 4545 | 115 | 240 | | 9.8 | 114 | 123.8 | 125 | 31 |
| SP8V 900-4 | 895 | 900 | 5050 | 125 | 265 | | 3.2 | 127 | 123.8 | 156 | 23 |
| SP8V 1000-4 | 995 | 1000 | 5050 | 125 | 265 | | 3.2 | 127 | 123.8 | 173 | 23 |
| SP8V 1250-4 | 1245 | 1250 | 6050 | 160 | 415 | | 3.2 | 127 | 123.8 | 303 | 23 |

| | | | | | | | | | | | |
|--------------|------|------|------|-----|-----|----|----|-----|-----|------|----|
| SP8V 300-6 | 295 | 300 | 4545 | 115 | | 46 | 21 | 114 | 181 | 43.6 | 26 |
| SP8V 315-6 | 310 | 315 | 4545 | 115 | | 46 | 21 | 114 | 181 | 49.9 | 26 |
| SP8V 335-6 | 330 | 335 | 4545 | 115 | | 46 | 21 | 114 | 181 | 58.7 | 26 |
| SP8V 355-6 | 350 | 355 | 4545 | 115 | | 46 | 21 | 114 | 181 | 68 | 26 |
| SP8V 375-6 | 370 | 375 | 4545 | 115 | | 46 | 21 | 114 | 181 | 78 | 26 |
| SP8V 400-6 | 395 | 400 | 4545 | 115 | 240 | 46 | 21 | 114 | 181 | 70.1 | 22 |
| SP8V 425-6 | 420 | 425 | 4545 | 115 | 240 | 46 | 21 | 114 | 181 | 76.8 | 22 |
| SP8V 450-6 | 445 | 450 | 4545 | 115 | 240 | 46 | 21 | 114 | 181 | 82.8 | 22 |
| SP8V 475-6 | 470 | 475 | 4545 | 115 | 240 | 46 | 21 | 114 | 181 | 82.6 | 29 |
| SP8V 500-6 | 495 | 500 | 4545 | 115 | 240 | 46 | 21 | 114 | 181 | 87.8 | 29 |
| SP8V 560-6 | 555 | 560 | 4545 | 115 | 240 | 46 | 21 | 114 | 181 | 102 | 29 |
| SP8V 630-6 | 625 | 630 | 5050 | 125 | 265 | 33 | 21 | 127 | 181 | 126 | 29 |
| SP8V 710-6 | 705 | 710 | 5050 | 125 | 265 | 33 | 21 | 127 | 181 | 145 | 29 |
| SP8V 710-6B | 705 | 710 | 6050 | 160 | 415 | 33 | 21 | 127 | 181 | 206 | 22 |
| SP8V 800-6 | 795 | 800 | 5050 | 125 | 265 | 33 | 21 | 127 | 181 | 168 | 29 |
| SP8V 800-6B | 795 | 800 | 6050 | 160 | 415 | 33 | 21 | 127 | 181 | 217 | 29 |
| SP8V 900-6 | 895 | 900 | 5050 | 125 | 265 | 33 | 21 | 127 | 181 | 196 | 29 |
| SP8V 900-6B | 895 | 900 | 6050 | 160 | 415 | 33 | 21 | 127 | 181 | 244 | 29 |
| SP8V 1000-6 | 995 | 1000 | 5050 | 125 | 265 | 33 | 21 | 127 | 181 | 219 | 29 |
| SP8V 1000-6B | 995 | 1000 | 6050 | 160 | 415 | 33 | 21 | 127 | 181 | 284 | 29 |
| SP8V 1250-6 | 1245 | 1250 | 6050 | 160 | 415 | 33 | 21 | 127 | 181 | 360 | 29 |

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合です。

*Bタイプはボス特大型です。