


適用8Vベルト

Unit : mm


品番 Part No.	データー径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 Mass	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SP8V 315-8	310	315	5050	125		30	81.2	127	238.2	57.4	26
SP8V 335-8	330	335	5050	125		30	81.2	127	238.2	67.6	26
SP8V 355-8	350	355	5050	125		30	81.2	127	238.2	78.5	26
SP8V 375-8	370	375	5050	125		30	81.2	127	238.2	90	26
SP8V 400-8	395	400	5050	125		30	81.2	127	238.2	105	26
SP8V 425-8	420	425	5050	125		30	81.2	127	238.2	122	26
SP8V 450-8	445	450	5050	125	265	30	81.2	127	238.2	119	22
SP8V 475-8	470	475	5050	125	265	30	81.2	127	238.2	118	22
SP8V 500-8	495	500	5050	125	265	30	81.2	127	238.2	119	22
SP8V 560-8	555	560	6050	160		30	81.2	127	238.2	209	26
SP8V 630-8	625	630	6050	160	415	30	81.2	127	238.2	204	22
SP8V 710-8	705	710	6050	160	415	30	81.2	127	238.2	235	22
SP8V 800-8	795	800	6050	160	415	30	81.2	127	238.2	247	29
SP8V 900-8	895	900	6050	160	415	30	81.2	127	238.2	279	29
SP8V 1000-8	995	1000	6050	160	415	30	81.2	127	238.2	328	29
SP8V 1250-8	1245	1250	6050	160	415	30	81.2	127	238.2	425	29

*質量はプーリ単体です。


*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合です。



22



26



29