



適用C.CXベルト

Unit : mm


品番 Part No.	デーラム径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
BTV 200-C5	200	209.6	11080	75		30	26	80	136	18	26
BTV 206-C5	206	215.6	11080	75		30	26	80	136	19.2	26
BTV 212-C5	212	221.6	11080	75		30	26	80	136	20.4	26
BTV 218-C5	218	227.6	11080	75		30	26	80	136	21.6	26
BTV 224-C5	224	233.6	11080	75		30	26	80	136	23	26
BTV 230-C5	230	239.6	11080	75		30	26	80	136	24.2	26
BTV 236-C5	236	245.6	11080	75		30	26	80	136	25.5	26
BTV 243-C5	243	252.6	11080	75		30	26	80	136	27.1	26
BTV 250-C5	250	259.6	11080	75		30	26	80	136	28	26
BTV 265-C5	265	274.6	11080	75	160	30	26	80	136	26	22
BTV 280-C5	280	289.6	11080	75	160	30	26	80	136	26	22
BTV 300-C5	300	309.6	11080	75	165	30	26	80	136	28	22
BTV 315-C5	315	324.6	11080	75	170	30	26	80	136	29	29
BTV 355-C5	355	364.6	11080	75	170	30	26	80	136	32	29
BTV 400-C5	400	409.6	13090	90	200	30	16	90	136	41	29
BTV 450-C5	450	459.6	13090	90	200	30	16	90	136	46	29
BTV 500-C5	500	509.6	13090	90	200	30	16	90	136	51	29
BTV 560-C5	560	569.6	13090	90	200	30	16	90	136	55	29
BTV 630-C5	630	639.6	13090	90	200	30	16	90	136	61	29
BTV 710-C5	710	719.6	13090	90	200	30	16	90	136	70	29
BTV 800-C5	800	809.6	13090	90	200	30	16	90	136	84	29



22



26



29

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーを適用する場合です。