



適用M.3V.3VX.SPZベルト

Unit : mm


品番 Part No.	データー径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SPZ 60-1	60	64	1008	25	59		6	22	16	0.31	1
SPZ 63-1	63	67	1108	28	62		6	22	16	0.27	1
SPZ 67-1	67	71	1108	28	62		6	22	16	0.32	1
SPZ 71-1	71	75	1108	28	62		6	22	16	0.36	1
SPZ 75-1	75	79	1108	28	62		6	22	16	0.44	1
SPZ 80-1	80	84	1210	32	75		9	25	16	0.5	1
SPZ 85-1	85	89	1210	32	86		9	25	16	0.7	1
SPZ 90-1	90	94	1210	32	86		9	25	16	0.76	1
SPZ 95-1	95	99	1210	32	86		9	25	16	0.84	1
SPZ 100-1	100	104	1210	32	86		9	25	16	0.92	1
SPZ 106-1	106	110	1610	42	92		9	25	16	0.95	1
SPZ 112-1	112	116	1610	42	92		9	25	16	1.1	1
SPZ 118-1	118	122	1610	42	92		9	25	16	1.2	1
SPZ 125-1	125	129	1610	42	92		9	25	16	1.5	1
SPZ 132-1	132	136	1610	42	92		9	25	16	1.7	1
SPZ 140-1	140	144	1610	42	92		9	25	16	1.9	1
SPZ 150-1	150	154	1610	42	92		9	25	16	2	1
SPZ 160-1	160	164	1610	42	92		9	25	16	2.3	1
SPZ 170-1	170	174	1610	42	92		9	25	16	2.5	1
SPZ 180-1	180	184	1610	42	92		9	25	16	2.3	2
SPZ 190-1	190	194	1610	42	92		9	25	16	3	2
SPZ 200-1	200	204	2012	50	106		16	32	16	3.4	2
SPZ 212-1	212	216	2012	50	106		16	32	16	3.6	2
SPZ 224-1	224	228	2012	50	106		16	32	16	3.8	2
SPZ 236-1	236	240	2012	50	106		16	32	16	4.4	2
SPZ 250-1	250	254	2012	50	106		16	32	16	4.6	2
SPZ 265-1	265	269	2012	50	106	8	8	32	16	5.1	3
SPZ 280-1	280	284	2012	50	106	8	8	32	16	5.6	3
SPZ 300-1	300	304	2012	50	106		16	32	16	6.7	2
SPZ 315-1	315	319	2012	50	106	8	8	32	16	7.3	3
SPZ 355-1	355	359	2012	50	106	8	8	32	16	7	4
SPZ 400-1	400	404	2012	50	106	8	8	32	16	8.5	4




1



2



3



4

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合があります。