



SPZ-4

適用M.3V.3VX.SPZベルト


Unit : mm




18




19



22



24



29

品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SPZ 63-4	63	67	1108	28		30		22	52	0.55	19
SPZ 67-4	67	71	1108	28		30		22	52	0.64	19
SPZ 71-4	71	75	1108	28		30		22	52	0.76	19
SPZ 75-4	75	79	1210	32		27		25	52	0.8	19
SPZ 80-4	80	84	1210	32		27		25	52	0.9	19
SPZ 85-4	85	89	1610	42		27		25	52	0.96	19
SPZ 90-4	90	94	1610	42		27		25	52	1.1	19
SPZ 95-4	95	99	1610	42		27		25	52	1.3	19
SPZ 100-4	100	104	1610	42			27	25	52	1.4	18
SPZ 106-4	106	110	1610	42			27	25	52	1.6	18
SPZ 112-4	112	116	2012	50			20	32	52	1.7	18
SPZ 118-4	118	122	2012	50			20	32	52	2	18
SPZ 125-4	125	129	2012	50			20	32	52	2.4	18
SPZ 132-4	132	136	2012	50			20	32	52	2.8	18
SPZ 140-4	140	144	2012	50			20	32	52	3.1	18
SPZ 150-4	150	154	2517	60			7	45	52	3.9	18
SPZ 160-4	160	164	2517	60			7	45	52	4.9	18
SPZ 170-4	170	174	2517	60			7	45	52	5.5	18
SPZ 180-4	180	184	2517	60			7	45	52	6.4	18
SPZ 190-4	190	194	2517	60			7	45	52	7.3	18
SPZ 200-4	200	204	2517	60	125	3.5	3.5	45	52	5.5	22
SPZ 212-4	212	216	2517	60	125	3.5	3.5	45	52	6.3	22
SPZ 224-4	224	228	2517	60	125	3.5	3.5	45	52	6.9	22
SPZ 236-4	236	240	2517	60	125	3.5	3.5	45	52	7.3	22
SPZ 250-4	250	254	2517	60	125	3.5	3.5	45	52	7.8	22
SPZ 265-4	265	269	2517	60	125	3.5	3.5	45	52	8.8	22
SPZ 280-4	280	284	2517	60	125	3.5	3.5	45	52	9.2	22
SPZ 300-4	300	304	2517	60	125	3.5	3.5	45	52	10	22
SPZ 315-4	315	319	2517	60	125	3.5	3.5	45	52	13.1	22
SPZ 355-4	355	359	2517	60	125	3.5	3.5	45	52	12.2	29
SPZ 400-4	400	404	2517	60	125	3.5	3.5	45	52	14.2	29
SPZ 450-4	450	454	3020	75	155	0.5	0.5	51	52	16.8	29
SPZ 500-4	500	504	3020	75	159	0.5	0.5	51	52	21.4	29
SPZ 630-4	630	634	3030	75	146	12	12	76	52	26.6	24

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合があります。