


適用M.3V.3VX.SPZベルト

Unit : mm


品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SPZ 85-5	85	89	1610	42		39		25	64	1.2	19
SPZ 90-5	90	94	1610	42		39		25	64	1.3	19
SPZ 95-5	95	99	1610	42		39		25	64	1.5	19
SPZ 100-5	100	104	2012	50		32		32	64	1.6	19
SPZ 106-5	106	110	2012	50		32		32	64	1.9	19
SPZ 112-5	112	116	2012	50			32	32	64	2.1	18
SPZ 118-5	118	122	2012	50			32	32	64	2.3	18
SPZ 125-5	125	129	2012	50			32	32	64	2.8	18
SPZ 132-5	132	136	2517	60			19	45	64	3	18
SPZ 140-5	140	144	2517	60			19	45	64	3.5	18
SPZ 150-5	150	154	2517	60			19	45	64	4.3	18
SPZ 160-5	160	164	2517	60			19	45	64	5.1	18
SPZ 170-5	170	174	2517	60			19	45	64	6	18
SPZ 180-5	180	184	2517	60			19	45	64	6.9	18
SPZ 190-5	190	194	2517	60			19	45	64	8	18
SPZ 200-5	200	204	2517	60		9.5	9.5	45	64	8.9	26
SPZ 212-5	212	216	2517	60	125	9.5	9.5	45	64	7	22
SPZ 224-5	224	228	2517	60	125	9.5	9.5	45	64	8.1	22
SPZ 236-5	236	240	2517	60	125	9.5	9.5	45	64	8.4	22
SPZ 250-5	250	254	2517	60	125	9.5	9.5	45	64	8.7	22
SPZ 265-5	265	269	2517	60	125	9.5	9.5	45	64	9.8	22
SPZ 280-5	280	284	2517	60	125	9.5	9.5	45	64	11.8	22
SPZ 300-5	300	304	2517	60	125	9.5	9.5	45	64	11.5	22
SPZ 315-5	315	319	2517	60	125	9.5	9.5	45	64	15.2	22
SPZ 355-5	355	359	2517	60	125	9.5	9.5	45	64	14	29
SPZ 400-5	400	404	3020	75	159	6.5	6.5	51	64	14.8	29
SPZ 450-5	450	454	3020	75	155	6.5	6.5	51	64	19.7	29
SPZ 500-5	500	504	3030	75	146	6	6	76	64	23.5	24
SPZ 630-5	630	634	3535	90	178	12.5	12.5	89	64	30.7	24

*質量はプーリ単体です。


*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合があります。




18




19




22



24



26



29