




SPB-1

適用B.BX.5V.5VX.SPBベルト

Unit : mm



品番 Part No.	データー径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SPB 100-1	100	107	1610	42				25	25	0.84	5
SPB 106-1	106	113	1610	42				25	25	0.97	5
SPB 112-1	112	119	1610	42				25	25	1.2	5
SPB 118-1	118	125	1610	42				25	25	1.3	5
SPB 125-1	125	132	1610	42				25	25	1.7	5
SPB 132-1	132	139	1610	42				25	25	1.8	5
SPB 140-1	140	147	1610	42				25	25	2.2	5
SPB 150-1	150	157	1610	42				25	25	2.6	5
SPB 160-1	160	167	1610	42				25	25	3.1	5
SPB 170-1	170	177	1610	42				25	25	3.4	5
SPB 180-1	180	187	1610	42				25	25	3.8	5
SPB 190-1	190	197	2012	50	112		7	32	25	4.6	1
SPB 200-1	200	207	2012	50	106		7	32	25	4.1	1
SPB 212-1	212	219	2012	50	106		7	32	25	5.1	2
SPB 224-1	224	231	2012	50	106		7	32	25	5.3	2
SPB 236-1	236	243	2012	50	106		7	32	25	5.7	2
SPB 250-1	250	257	2012	50	106		7	32	25	6.2	2
SPB 280-1	280	287	2012	50	110		7	32	25	6.7	2
SPB 300-1	300	307	2012	50	110		7	32	25	8.5	2
SPB 315-1	315	322	2012	50	110		7	32	25	9.5	2

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合です。