



適用B.BX.5V.5VX.SPBベルト


Unit : mm




18




19




22




23



24



26



29

品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
SPB 125-5	125	132	2012	50			69	32	101	3.8	18
SPB 132-5	132	139	2517	60		56		45	101	3.8	19
SPB 135-5	135	142	2012	50		34.5	34.5	32	101	4.2	26
SPB 140-5	140	147	2517	60		28	28	45	101	4.8	26
SPB 145-5	145	152	2517	60		28	28	45	101	5.2	26
SPB 150-5	150	157	2517	60		28	28	45	101	5.7	26
SPB 155-5	155	162	2517	60		28	28	45	101	6.1	26
SPB 160-5	160	167	2517	60		28	28	45	101	6.7	26
SPB 165-5	165	172	2517	60		28	28	45	101	7.1	26
SPB 170-5	170	177	3020	75		25	25	51	101	7	26
SPB 175-5	175	182	3020	75		25	25	51	101	7.3	26
SPB 180-5	180	187	3020	75		25	25	51	101	7.9	26
SPB 185-5	185	192	3020	75		25	25	51	101	8.4	26
SPB 190-5	190	197	3020	75		25	25	51	101	9	26
SPB 195-5	195	202	3020	75		25	25	51	101	9.8	26
SPB 200-5	200	207	3020	75		25	25	51	101	10.5	26
SPB 206-5	206	213	3020	75		25	25	51	101	11.3	26
SPB 212-5	212	219	3020	75		25	25	51	101	12.1	26
SPB 218-5	218	225	3020	75		25	25	51	101	12.9	26
SPB 224-5	224	231	3020	75		25	25	51	101	13.8	26
SPB 230-5	230	237	3535	90			12	89	101	17.9	18
SPB 236-5	236	243	3535	90			12	89	101	19.4	18
SPB 250-5	250	257	3535	90			12	89	101	22.8	18
SPB 265-5	265	272	3535	90	175	6	6	89	101	19.3	22
SPB 280-5	280	287	3535	90	175	6	6	89	101	22.9	22
SPB 300-5	300	307	3535	90	175	6	6	89	101	23.4	22
SPB 315-5	315	322	3535	90	175	6	6	89	101	25.3	22
SPB 335-5	335	342	3535	90	175	6	6	89	101	27.1	22
SPB 355-5	355	362	3535	90	175	6	6	89	101	28.9	22
SPB 375-5	375	382	3535	90	175	6	6	89	101	29.4	29
SPB 400-5	400	407	3535	90	175	6	6	89	101	30.3	29
SPB 425-5	425	432	3535	90	175	6	6	89	101	31.6	29
SPB 450-5	450	457	3535	90	175	6	6	89	101	32.3	29
SPB 475-5	475	482	3535	90	175	6	6	89	101	35.3	29
SPB 500-5	500	507	3535	90	175	6	6	89	101	41	29
SPB 560-5	560	567	4040	100	210		1	102	101	47.6	23
SPB 630-5	630	637	4040	100	210		1	102	101	53.6	23
SPB 710-5	710	717	4040	100	215		1	102	101	71.3	23
SPB 800-5	800	807	4040	100	215		1	102	101	80.3	23
SPB 900-5	900	907	4545	115	240	6.5	6.5	114	101	94.6	24
SPB 1000-5	1000	1007	4545	115	240	6.5	6.5	114	101	112	24

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合です。