



適用C.CX.ベルト


Unit : mm



22



26



29

| 品番 Part No. | データー径 dn | 外径 D | ブッシング Bushing | | ボス部 Hub | | | | リム幅 W | 質量 (kg) | 形状図番 Type |
|----------------|-------------|---------|------------------|-------------------|------------|-------|-------|-----|----------|------------|--------------|
| | | | 品番 No. | 最大軸穴径 Max.Bore | d | t1 | t2 | l | | | |
| SPC 200-6 | 200 | 209.6 | 3535 | 90 | | 36.25 | 36.25 | 89 | 161.5 | 15.4 | 26 |
| SPC 212-6 | 212 | 221.6 | 3535 | 90 | | 36.25 | 36.25 | 89 | 161.5 | 18.2 | 26 |
| SPC 224-6 | 224 | 233.6 | 3535 | 90 | | 36.25 | 36.25 | 89 | 161.5 | 20.3 | 26 |
| SPC 236-6 | 236 | 245.6 | 3535 | 90 | | 36.25 | 36.25 | 89 | 161.5 | 24 | 26 |
| SPC 250-6 | 250 | 259.6 | 3535 | 90 | | 36.25 | 36.25 | 89 | 161.5 | 29.3 | 26 |
| SPC 265-6 | 265 | 274.6 | 3535 | 90 | | 36.25 | 36.25 | 89 | 161.5 | 31.7 | 26 |
| SPC 280-6 | 280 | 289.6 | 3535 | 90 | 175 | 36.25 | 36.25 | 89 | 161.5 | 31.2 | 22 |
| SPC 300-6 | 300 | 309.6 | 3535 | 90 | 175 | 36.25 | 36.25 | 89 | 161.5 | 31.9 | 22 |
| SPC 315-6 | 315 | 324.6 | 3535 | 90 | 175 | 36.25 | 36.25 | 89 | 161.5 | 33.7 | 22 |
| SPC 335-6 | 335 | 344.6 | 3535 | 90 | 175 | 36.25 | 36.25 | 89 | 161.5 | 35.4 | 22 |
| SPC 355-6 | 355 | 364.6 | 3535 | 90 | 175 | 36.25 | 36.25 | 89 | 161.5 | 37.3 | 22 |
| SPC 375-6 | 375 | 384.6 | 4040 | 100 | 210 | 29.75 | 29.75 | 102 | 161.5 | 41.8 | 22 |
| SPC 400-6 | 400 | 409.6 | 4040 | 100 | 210 | 29.75 | 29.75 | 102 | 161.5 | 47.1 | 22 |
| SPC 425-6 | 425 | 434.6 | 4040 | 100 | 210 | 29.75 | 29.75 | 102 | 161.5 | 53.1 | 22 |
| SPC 450-6 | 450 | 459.6 | 4545 | 115 | 240 | 23.75 | 23.75 | 114 | 161.5 | 62.6 | 22 |
| SPC 475-6 | 475 | 484.6 | 4545 | 115 | 240 | 23.75 | 23.75 | 114 | 161.5 | 66.7 | 22 |
| SPC 500-6 | 500 | 509.6 | 4545 | 115 | 240 | 23.75 | 23.75 | 114 | 161.5 | 70.6 | 29 |
| SPC 530-6 | 530 | 539.6 | 5050 | 125 | 265 | 17.25 | 17.25 | 127 | 161.5 | 85.1 | 29 |
| SPC 560-6 | 560 | 569.6 | 5050 | 125 | 265 | 17.25 | 17.25 | 127 | 161.5 | 85.4 | 29 |
| SPC 630-6 | 630 | 639.6 | 5050 | 125 | 265 | 17.25 | 17.25 | 127 | 161.5 | 103 | 29 |
| SPC 710-6 | 710 | 719.6 | 5050 | 125 | 265 | 17.25 | 17.25 | 127 | 161.5 | 112 | 29 |
| SPC 800-6 | 800 | 809.6 | 5050 | 125 | 267 | 17.25 | 17.25 | 127 | 161.5 | 141 | 29 |
| SPC 900-6 | 900 | 909.6 | 5050 | 125 | 265 | 17.25 | 17.25 | 127 | 161.5 | 154 | 29 |
| SPC 1000-6 | 1000 | 1009.6 | 5050 | 125 | 265 | 17.25 | 17.25 | 127 | 161.5 | 158 | 29 |

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーまたは、シャローキーを適用する場合です。