




## 適用A.AXベルト

Unit : mm

品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
BTV 63-A1	63	68.5	3622	22	56		5	25	20	0.45	1
BTV 67-A1	67	72.5	3622	22	56		5	25	20	0.51	1
BTV 71-A1	71	76.5	4225	30	63		5	25	20	0.57	1
BTV 75-A1	75	80.5	4225	30	63		5	25	20	0.63	1
BTV 80-A1	80	85.5	4225	30	63		5	25	20	0.71	1
BTV 83-A1	83	88.5	4225	30	63		5	25	20	0.76	1
BTV 85-A1	85	90.5	4225	30	63		5	25	20	0.8	1
BTV 88-A1	88	93.5	4225	30	63		5	25	20	0.86	1
BTV 90-A1	90	95.5	4225	30	63		5	25	20	0.9	1
BTV 93-A1	93	98.5	4225	30	63		5	25	20	0.96	1
BTV 95-A1	95	100.5	4225	30	63		5	25	20	1	1
BTV 98-A1	98	103.5	4225	30	63		5	25	20	1.06	1
BTV 100-A1	100	105.5	4225	30	63		5	25	20	1.1	1
BTV 103-A1	103	108.5	4225	30	63		5	25	20	1.2	1
BTV 106-A1	106	111.5	4225	30	63		5	25	20	1.3	1
BTV 109-A1	109	114.5	4225	30	63		5	25	20	1.35	1
BTV 112-A1	112	117.5	4225	30	63		5	25	20	1.4	1
BTV 118-A1	118	123.5	4225	30	63		5	25	20	1.6	1
BTV 125-A1	125	130.5	4225	30	63		5	25	20	1.7	1
BTV 132-A1	132	137.5	4225	30	67		5	25	20	1.5	2
BTV 140-A1	140	145.5	4225	30	67		5	25	20	1.6	2
BTV 150-A1	150	155.5	5035	35	80		15	35	20	2.2	2
BTV 160-A1	160	165.5	5035	35	80		15	35	20	2.3	2
BTV 170-A1	170	175.5	5035	35	80		15	35	20	2.5	2
BTV 180-A1	180	185.5	5035	35	80		15	35	20	2.7	2
BTV 190-A1	190	195.5	5035	35	80		15	35	20	2.8	2
BTV 200-A1	200	205.5	5035	35	80		15	35	20	2.9	6
BTV 212-A1	212	217.5	5035	35	80		15	35	20	3	6
BTV 224-A1	224	229.5	5035	35	80		15	35	20	3.1	6
BTV 250-A1	250	255.5	5035	35	80		15	35	20	3.5	6
BTV 280-A1	280	285.5	5035	35	80		15	35	20	3.9	6
BTV 300-A1	300	305.5	6340	45	100		20	40	20	4.8	6
BTV 315-A1	315	320.5	6340	45	100		20	40	20	5.2	6
BTV 355-A1	355	360.5	6340	45	100		20	40	20	5.9	6
BTV 400-A1	400	405.5	6340	45	100		20	40	20	7.5	6
BTV 450-A1	450	455.5	6340	45	100		20	40	20	8.6	6
BTV 500-A1	500	505.5	6340	45	100		20	40	20	9.8	6



\*質量はプーリ単体です。

\*最大軸穴径は新JIS平行キーを適用する場合です。