



適用A.AXベルト

Unit : mm


品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
BTV 80-A3	80	85.5	4225	30		15	10	25	50	1.1	26
BTV 83-A3	83	88.5	4225	30		15	10	25	50	1.2	26
BTV 85-A3	85	90.5	4225	30		15	10	25	50	1.3	26
BTV 88-A3	88	93.5	5035	35		15		35	50	1.5	19
BTV 90-A3	90	95.5	5035	35		15		35	50	1.6	19
BTV 93-A3	93	98.5	5035	35		15		35	50	1.65	19
BTV 95-A3	95	100.5	5035	35		15		35	50	1.7	19
BTV 98-A3	98	103.5	5035	35		15		35	50	1.8	19
BTV 100-A3	100	105.5	5035	35		15		35	50	1.9	19
BTV 103-A3	103	108.5	5035	35		15		35	50	2.1	19
BTV 106-A3	106	111.5	5035	35		15		35	50	2.2	19
BTV 109-A3	109	114.5	5035	35		15		35	50	2.3	19
BTV 112-A3	112	117.5	5035	35		15		35	50	2.4	19
BTV 118-A3	118	123.5	5035	35		15		35	50	2.7	19
BTV 125-A3	125	130.5	5035	35		15		35	50	3.1	19
BTV 132-A3	132	137.5	6340	45		10		40	50	3.7	19
BTV 140-A3	140	145.5	6340	45		10		40	50	4.2	19
BTV 150-A3	150	155.5	6340	45		10		40	50	4.8	19
BTV 160-A3	160	165.5	6340	45	90	5	5	40	50	4.5	22
BTV 170-A3	170	175.5	6340	45	90	5	5	40	50	4.9	22
BTV 180-A3	180	185.5	6340	45	90	5	5	40	50	5.3	22
BTV 190-A3	190	195.5	6340	45	90	5	5	40	50	5.8	22
BTV 200-A3	200	205.5	6340	45	100	5	5	40	50	5.3	22
BTV 212-A3	212	217.5	6340	45	100	5	5	40	50	5.4	22
BTV 224-A3	224	229.5	6340	45	100	5	5	40	50	5.5	22
BTV 250-A3	250	255.5	6340	45	100	5	5	40	50	6.1	22
BTV 280-A3	280	285.5	6340	45	100	5	5	40	50	6.7	22
BTV 300-A3	300	305.5	8545	65	132	5		45	50	9.1	28
BTV 315-A3	315	320.5	8545	65	132	5		45	50	9.4	28
BTV 355-A3	355	360.5	8545	65	132	5		45	50	10	28
BTV 400-A3	400	405.5	8545	65	132	5		45	50	12	28
BTV 450-A3	450	455.5	8545	65	132	5		45	50	13.5	28
BTV 500-A3	500	505.5	8545	65	132	5		45	50	15.5	28
BTV 560-A3	560	565.5	8545	65	132	5		45	50	17	28




19



22



26



28

*質量はプーリ単体です。

*最大軸穴径は新JIS平行キーを適用する場合です。