



# BTV C-6

## 適用C.CXベルト


Unit : mm



22



26



29

品番 Part No.	データ径 dn	外径 D	ブッシング Bushing		ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
			品番 No.	最大軸穴径 Max.Bore	d	t1	t2	l			
BTV 200-C6	200	209.6	11080	75		30	51.5	80	161.5	19.6	26
BTV 206-C6	206	215.6	11080	75		30	51.5	80	161.5	20.8	26
BTV 212-C6	212	221.6	11080	75		30	51.5	80	161.5	22	26
BTV 218-C6	218	227.6	11080	75		30	51.5	80	161.5	23.3	26
BTV 224-C6	224	233.6	11080	75		30	51.5	80	161.5	24.6	26
BTV 230-C6	230	239.6	11080	75		30	51.5	80	161.5	26	26
BTV 236-C6	236	245.6	11080	75		30	51.5	80	161.5	27.5	26
BTV 243-C6	243	252.6	11080	75		30	51.5	80	161.5	29	26
BTV 250-C6	250	259.6	11080	75		30	51.5	80	161.5	31	26
BTV 265-C6	265	274.6	11080	75		30	51.5	80	161.5	34.5	26
BTV 280-C6	280	289.6	11080	75	160	50	31.5	80	161.5	30	22
BTV 300-C6	300	309.6	11080	75	165	50	31.5	80	161.5	31	22
BTV 315-C6	315	324.6	11080	75	165	50	31.5	80	161.5	33	22
BTV 355-C6	355	364.6	13090	90	200	50	21.5	90	161.5	42	22
BTV 400-C6	400	409.6	13090	90	200	50	21.5	90	161.5	45	29
BTV 450-C6	450	459.6	13090	90	200	50	21.5	90	161.5	49	29
BTV 500-C6	500	509.6	13090	90	200	50	21.5	90	161.5	55	29
BTV 560-C6	560	569.6	13090	90	200	50	21.5	90	161.5	60	29
BTV 630-C6	630	639.6	13090	90	200	50	21.5	90	161.5	66	29
BTV 710-C6	710	719.6	13090	90	200	50	21.5	90	161.5	76	29

\*質量はプーリ単体です。

\*最大軸穴径は新JIS平行キーを適用する場合です。