



## 適用A,AXベルト

Unit : mm


品番 Part No.	デーラム径 dn	外径 D	下穴径 ds	最大軸穴径 Max.Bore	ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
					d	t1	t2	l			
2	41.8	50.8	13	14	38	16		68	52	0.6	①-1
2 1/2	54.5	63.5	13	24	47	16		68	52	1.0	①-1
3	67.2	76.2	13	28			19	33	52	1.2	④-1
			13	28	50	19	33	38	52		②-1
3 1/2	79.9	88.9	13	30			19	33	52	1.7	④-1
			13	28	50	19	33	38	52		②-1
4	92.6	101.6	13	35			19	33	52	1.8	④-1
			13	28	50	19	33	38	52		②-1
4 1/2	105.3	114.3	15	40			19	33	52	2.3	④-1
			15	32	58	19	33	38	52		②-1
5	118.0	127.0	15	50			19	33	52	2.8	④-1
			15	32	58	19	33	38	52		②-1
5 1/2	130.7	139.7	15	55			19	33	52	3.1	④-1
			15	32	58	19	33	38	52		②-1
6	143.4	152.4	15	35	62	7	7	38	52	3.0	⑤-2
6 1/2	156.1	165.1	15	35	62	7	7	38	52	3.4	⑤-2
7	168.8	177.8	15	35	62	7	7	38	52	3.3	⑤-2
8	194.2	203.2	15	35	65	7	7	38	52	4.0	⑤-2
9	219.6	228.6	15	42	75	5	5	42	52	4.6	⑤-2
10	245.0	254.0	15	42	75	5	5	42	52	5.0	⑤-2
11	270.4	279.4	15	42	75	5	5	42	52	5.6	⑤-2
12	295.8	304.8	15	42	75	5	5	42	52	5.9	⑤-2
13	321.2	330.2	15	45	82	5	5	42	52	6.0	⑤-2
14	346.6	355.6	18	45	82	5	5	42	52	7.0	⑤-2
15	372.0	381.0	18	50	88	5	5	42	52	8.2	⑤-2
16	397.4	406.4	20	50	88	5	5	42	52	7.8	⑤-2
18	448.2	457.2	20	50	88	5	5	42	52	11.3	⑤-2
20	499.0	508.0	20	50	90	5	5	42	52	12.8	⑤-2
22	549.8	558.8	20	50	90	5	5	42	52	14.1	⑤-2
24	600.6	609.6	20	53	95	5	5	42	52	14.8	⑤-2




①-1



②-1



④-1



⑤-2