

適用B,BXベルト

Unit : mm

品番 Part No.	データー径 dn	外径 D	下穴径 ds	最大軸穴径 Max.Bore	ボス部 Hub				リム幅 W	質量 (kg)	形状図番 Type
					d	t1	t2	l			
3	65.2	76.2	15	28			44	40	84	1.5	④-1
3 1/2	77.9	88.9	15	30			44	40	84	2.0	④-1
4	90.6	101.6	15	35			44	40	84	2.7	④-1
4 1/2	103.3	114.3	15	40			44	40	84	3.2	④-1
5	116.0	127.0	18	50			44	40	84	4.1	④-1
5 1/2	128.7	139.7	18	55			44	40	84	5.0	④-1
6	141.4	152.4	18	42	76	15	15	54	84	5.0	⑤-2
6 1/2	154.1	165.1	18	42	76	15	15	54	84	5.0	⑤-2
7	166.8	177.8	20	46	83	13	13	58	84	6.1	⑤-2
8	192.2	203.2	20	46	83	13	13	58	84	7.0	⑤-2
9	217.6	228.6	20	46	83	13	13	58	84	7.0	⑤-2
10	243.0	254.0	20	50	88	13	13	58	84	8.5	⑤-2
11	268.4	279.4	22	50	88	13	13	58	84	8.9	⑤-2
12	293.8	304.8	22	50	88	13	13	58	84	9.9	⑤-2
13	319.2	330.2	22	50	88	13	13	58	84	10.4	⑤-2
14	344.6	355.6	22	50	88	13	13	58	84	11.8	⑤-2
15	370.0	381.0	22	52	95	11	11	62	84	13.0	⑤-2
16	395.4	406.4	22	52	95	11	11	62	84	14.1	⑤-2
18	446.2	457.2	22	52	95	11	11	62	84	16.4	⑤-2
20	497.0	508.0	25	52	95	11	11	62	84	19.5	⑤-2
22	547.8	558.8	25	56	102	11	11	62	84	20.8	⑤-2
24	598.6	609.6	25	58	105	11	11	62	84	22.7	⑤-2
26	649.4	660.4	25	60	108	11	11	62	84	26.8	⑤-2
28	700.2	711.2	25	60	108	11	11	62	84	31.0	⑤-2

